

PRINTRONIX®
AUTO ID

T800

DESKTOP THERMAL PRINTER

PRODUCTIVITY

VERSATILITY

DEPENDABILITY





Industrial Printer Features in a Desktop Printer

The T800 is a high-performance, thermal desktop printer with enterprise-level productivity, dependable performance and a selection of versatile high-end features such as RFID, WiFi and advanced security protocols. The T800 is Printronix's first desktop printer to incorporate its renowned Printronix System Architecture (PSA) and includes a full suite of labor-saving features and printer management tools for easy day-to-day operations.



ENTERPRISE-LEVEL PRODUCTIVITY

- Fast print speed of 8 ips
- High-performance ARM A7 processor for fast time-to-first-print and label throughput
- Large 300-meter ribbon for fewer roll changes
- Can easily print over 1,000 labels per day
- Easy to operate



VERSATILE FEATURES

- Optional RFID capability with adjustable antenna and auto calibration
- Extensive connectivity options: Std: Ethernet, USB host, USB device, RS232
- Optional: WiFi 802.11 a/b/g/n/ac, Bluetooth 4.2
- Compatible with PrintNet Enterprise printer management tool
- Enterprise-level encryption and security protocols
- Ten printer emulations for seamless installations



DEPENDABLE PERFORMANCE

- Solid double-wall clamshell construction
- Wide operating temperature range of 5° C to 40° C
- High MTBF of 8,000 hours
- Built on the proven Printronix System Architecture (PSA) platform

TRACKING IN REAL TIME WITH RFID



The T800 with optional UHF RFID was designed to meet the growing demand for encoding and printing RFID labels at an affordable price. Retail, manufacturing, and healthcare are just a few of the industries that use RFID to track products throughout the supply chain, take inventory in real-time or locate equipment within the enterprise.

The T800 makes printer setup for encoding and printing of RFID labels fast and easy. Not only can it support labels down to .625 inches in length, but the antenna can be adjusted for non-standard inlay positions. Further, the RFID label calibration function automatically sets the optimal label encoding position within the printer.



WHAT DOES ENTERPRISE-LEVEL PRODUCTIVITY MEAN?

- The printer includes the tools to install, configure and troubleshoot multiple printers at once
- Printers are fast and reliable for maximum productivity
- The time required to perform day-to-day tasks has been minimized
- Includes multiple connectivity options and advanced security protocols



NOW INCLUDED!

T800 is the first Printronix desktop thermal printer built on the PSA platform. In the past, PSA has been limited to our high-end industrial printers.

PSA is an intelligent design platform that combines advanced features with a common set of building blocks to simplify printer installation, operation, and improve productivity. Partners familiar with one Printronix printer can easily work with any of our printers.

ENTERPRISE PRODUCTIVITY

EASE OF INSTALLATION



Drop-in installation with minimal setup & multiple emulations

EASE OF MAINTENANCE



Remotely troubleshoot & monitor printer status

RELIABLE LABEL PRODUCTION



Easy to use large color LCD display with intuitive icon-driven menu



Easy to configure control panel or with interactive webpage



Push firmware & re-configure printers in batches

Fast print speed and time-to-first-print

Full suite of connectivity options & security protocols



Easy printer swap with quick change memory card (QCMC)

More uptime with easy load media and large ribbon rolls



Commonality of operation between all Printronix printers

Dependable production up to 1,000 labels per day

T800

SPECIFICATIONS



PRODUCT BENEFITS

- * High performance ARM Cortex-A7
- * Re-enforced plastic enclosure
- * Transfer and direct printing
- * Four-inch print width
- * Printronix Systems Architecture (PSA)
- * Ethernet 10/100 BaseT (Standard)
- * Premium Asian Fonts (Option)
- * On-Pitch RFID, multi-position antenna
- * Available in 203 DPI and 300 DPI
- * 128MB RAM / 128MB Flash Memory
- * Color 3.5in LCD nine-key control panel
- * 4-32 GB SD memory card capability
- * WiFi 802.11 a/b/g/n/ac (Option)
- * Bluetooth 4.2 (Option)
- * ENERGY STAR Certified

PRINTER SPECIFICATIONS

Max Print Speed	8 IPS @ 203 DPI, 6IPS @ 300 DPI
Print Method	Transfer and Direct
Resolution	203 DPI / 300 DPI
Max. Print Width	4.1" (104mm)

MEDIA SPECIFICATIONS

Media Type	Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets
Min. Media Width	0.79" (20mm)
Max. Media Width	4.4" (112mm)
Min. Media Length	Continuous 0.25", Tear-Off / Peel-Off 1.0"
Max. Media Length	Up to 50"
Media Thickness	0.00236" (0.06mm) to 0.00784" (0.19mm)
Media Roll Core Diameter	1.0" (25.4mm), 1.5" (38mm)
Max. Media Roll Diameter	5.0" (127mm),
Media Sensing	Gap, Mark

RIBBON SPECIFICATIONS

Ribbon Type	Wax, Wax/Resin, Resin
Min. Ribbon Width	1.0" (25.4mm)
Max. Ribbon Width	4.33" (110mm)
Max. Ribbon Length	300 Meters
Ribbon Core Diameter	.5" (12.7mm), 1.0" (25.4mm)

PHYSICAL CHARACTERISTICS

Width	8.3" (210mm)
Height	7.5" (190mm)
Depth	11.2" (285mm)
Printer Weight	6.79 lbs.(2.9Kg)
Shipping Weight	9.47 lbs.(4.3Kg)

PRINTER LANGUAGE

Printer Languages (Native / Competitor)	PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL/EGL
Legacy Line Printer Emulations	P-Series / XQ, Proprietary, Serial Matrix, Epson FX
Job Control Languages	PJL, XML, and PTX-SETUP

COMMUNICATION AND CONNECTIVITY/INTERFACE

Standard Interface I/O	Serial RS232, USB Device (Type B), USB Host (Type A) and Ethernet 10/100Base T
Optional Interface I/O	WiFi (802.11a/b/g/n/ac), (WiFi Alliance Certified) Bluetooth 4.2
WiFi Security Encryption	WEP 40/128bit, TKIP, AES CCMP
WiFi Security Authentication	WPA/WPA2, PSK, EAP-TTLS, EAP-PEAP, LEAP, PEAPv1/PEAP-TLS, PEAPv0/MS-CHAPv2

RFID

Radio	UHF EPC Gen2 / ISO18000-6C
Antenna	Multi-position RF Antenna
Inlays	On-Pitch label to 0.625 in (depending on inlay) RFID label calibration
Languages	PGL, ZPL, STGL, MGL
Counters	Tracks good / overstruck labels

MEDIA HANDLING MODES

Standard	Continuous, Tear-Off
Options	Peel-Off, Cut

OPERATING ENVIRONMENT

Operating Temperature	40 to 104°F (5 to 40°C)
Operating Humidity	25-85% Non-Condensing
Storage Temperature	-40 to 140°F (-40 to +60°C)
Storage Humidity	10 - 90% Non-Condensing

POWER REQUIREMENT

Line Input	Auto Range 100 - 240 VAC (48 - 62 Hz)
------------	---------------------------------------

REGULATORY COMPLIANCES

Emissions	FCC, CE, IC, CCC, KC
Safety	cTUVus, CE, IC, EAC, SMARK, NOM, CCC, KC, BIS, BSMI
Environmental	RoHS, WEEE, Energy Star
RFID	FCC, IC, CE, CCC, NCC, NTC, WPC
WiFi/BT	FFC, IC, CE, CCC
Energy Savings	Energy Star 2.0

BAR CODE SYMBOLOGIES

1D Barcodes	BC-412, Code 11, Code 39, Code35, Code 93, Codabar, Code 128 Subsets A/B/C, Industrial 2 of 5, Interleave 2 of 5, German 1-2/5, EAN-8, EAN-13, UCC/EAN-128, UPC-A, UPC-E, UPCSHIP, UPS 11, MSI, Matrix 2 of 5, PLESSEY, POSTNET, 4-state PostBar, Australian 4-state, FIM, ITF14, TELEPEN, PLANET, USPS Intelligent Mail, LOGMARS
2D Barcodes	PDF-417, MicroPDF-417, Maxicode, DataMatrix, QR Codes, Aztec, GS1 Databar (RSS-14)

FONT, GRAPHIC SUPPORT

Graphic Formats	PCX, TIFF, BMP, PNG
Font Technologies	Intellifont, TrueType, Unicode
Standard Fonts	OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate/Bold/Condensed
Premium Asian Fonts (SD card)	Simplified Chinese, Japanese, Korean, Thai

REMOTE MANAGEMENT SOFTWARE

PrintNet Enterprise	Enterprise Grade Remote Management Solution
---------------------	---

OPTIONS AND ACCESSORIES

* WiFi 802.11 a/b/g/n/ac	* UHF RFID (US 902-928MHz, EU 866-868MHz)
* Bluetooth 4.2	* Premium Asian Font Cards (SD Card)
* Cutter	* External 3in Supply Roll Dispenser
* Peeler	* QCMC (Quick Change Memory Card) (SD-Card)



Contact your local Printronix Auto ID authorized reseller.

PRINTRONIX
AUTO ID

printronixautoid.com



© 2018 Printronix Auto ID, Inc. All rights reserved. Printronix Auto ID and all product names, numbers and logos are trademarks or registered trademarks of Printronix, Inc. Product appearance and/or specifications are subject to change without notice. Windows® is a registered trademark of Microsoft Corporation™ in the United States and other countries. All other trademarks, product names and company names and logos herein, are the property of their respective owners. (9/18)