Fast, Full-Color Label Printer for Just In Time Color Printing



Epson Color Works[™] C3500 Color Inkjet Label Printer



- Compact, robust design for commercial use
- High print speed of up to 4 inches/second¹
- High-quality, four-color inkjet printing (CMYK)
- Individual ink cartridges for efficient use of ink
- Supports all major label applications
- Meets BS5609 certification²
- USB and Ethernet interfaces

Now you can dramatically reduce label costs, increase operational efficiencies and quickly produce high-quality color labels with Just in Time Color™ printing on Epson's high-speed ColorWorks C3500 printer.

Color labels are the new standard

Today there is a growing demand for the use of color labels that feature color codes, photos and pictograms to highlight relevant information. This trend sharply drives up the number of label variations and increases label production complexity. Epson's ColorWorks C3500's ability to produce full color labels on demand makes it the ideal solution.

Advanced features only from Epson

Epson's compact, four-color C3500 inkjet printer features fast printing speeds up to 4 inches/second, a banding reduction mode and a nozzle check system that produces a reliable output of high volume labels with excellent image quality. In addition, it offers multiple easy-to-use features such as an autocutter, easy paper loading and an LCD with printer status readouts.

Superior print and ink quality

Epson's patented MicroPiezo® inkjet technology together with our DURABrite® Ultra Pigment ink ensures labels with crisp, clear, easy-to-read text and barcodes and vibrant graphics that resist smudges and water even on plain paper. And with the C3500 you can print on a wide range of media from plain, synthetic and matte to glossy stock. It handles roll-fed or fanfold, die cut or continuous label media.

Significantly lower your costs

With Epson's C3500 printer you can dramatically reduce the cost of your label operations. Instead of maintaining an expensive inventory of preprinted labels, you can print the labels you need when you need them. In addition, the C3500 features individual ink cartridges for a more efficient use of ink and a very low cost of maintenance.

Reliable and flexible

Designed for high-duty commercial environments, the rugged C3500 is dust and water-resistant and built to last. It has an MTBF of 88 thousand hours.³

Backed by the leader

The ColorWorks C3500 delivers the quality and reliability that Epson is known for and is backed by Epson's industry-leading service and support programs.



Printer

Print method MicroPiezo® inkjet technology, Automatic Nozzle

Checking

Pigmented ink, individual CMYK cartridges Ink type4 Print resolution 360 dpi x 360 dpi — Speed Mode 720 dpi x 360 dpi — Quality Mode

360 dpi x 360 dpi — Banding Reduction disabled 4.0"/sec. (2.2" print width) 3.4"/sec. (4.1" print width) Print speed (max.)

360 dpi x 360 dpi — Banding Reduction enabled 3.7"/sec. (2.2" print width) 3.1"/sec. (4.1" print width)

720 dpi x 360 dpi — Banding Reduction enabled

2.0"/sec. (2.2" print width) 1.7"/sec. (4.1" print width)

4.1" (104mm) max. Print width

Media types Roll-fed or fanfold; die cut or continuous; single layer

or adhesive labels on liner; plain paper, fine paper, PET

Media dimensions

1.2"-4.25" (30-108mm) — roll feed 2.0"-4.25" (50-108mm) — fan fold Width

Thickness 4.7-7.5mils (0.12-0.19mm) O.D. 4.0" (102mm) max. Roll size

Core diameter 1.75" (44mm) to 2.25" (57mm)

Gap, black mark, media cut Media sensors

Die-cut label gap Min. 0.12" (3.0mm)

Black mark size Min. 0.20 x 0.16" (5.0 x 4.0mm) (W x H)

General

Operating system

Interfaces USB 2.0 High-speed, Ethernet 10/100 BASE-T

Microsoft® Windows® XP 32-bit (SP3)/64-bit (SP2), Vista® 32-bit/64-bit (SP2), Windows 7 32-bit/64-bit

(SP1), Windows 8 32-bit/64-bit

Barcode font UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, (Built-in driver)

ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar

Stacked Omnidirectional, GS1 DataBar Expanded

Stacked, DataMatrix, Aztec Code⁵

10-35 degrees C / 20-80% RH humidity Operating temperature Storage temperature -20-40 degrees C / 5-85% RH humidity 12.2" x 11.1" x 10.3" (W x D x H) — Printer 17.5" x 15.5" x 16.8" (W x D x H) — Shipping Overall dimensions

26 lbs (12.2 kg) — Printer (without ink) 41 lbs (12.2 kg) — Shipping Weight (Approx.)

Power consumption 30 W Printing (average printing)

2.5 W Standby 0.3 W Power Off state

Rated voltage AC 100-240 VAC

Rated frequency 50-60 Hz Approx. 58 dBA Acoustic noise EMI FCC / ICES-003 Class B

Safety standards UL60950-1/CSA C22.2 No.60950-1

One year depot repair Warranty

What's in the box

ColorWorks C3500

AC power adapter with line cord Full capacity Ink cartridges

Sample label roll Media output tray Instruction sheet

CD with utilities and manuals



Ordering information

		Model Number
TM-C3500 Inkjet Printer		C31CD54011
GJIC22P(C) Ink Cartridge	Cyan	C33S020581
GJIC22P (K) Ink Cartridge	Black	C33S020577
GJIC22P (M) Ink Cartridge	Magenta	C33S020582
GJIC22P (Y) Ink Cartridge	Yellow	C33S020583
SJMB3500 Maintenance Box		C33S020580



Color-coded labels enable fast, accurate product identification.



The C3500 using Epson pigment inks is BS5609 certified for GHS labels.2

Speed is printing 2.2" (56mm) width bidirectional mode, with banding reduction disabled in 360×360 dpi resolution.

²Epson's ColorWorks C3500 inkjet printer with Epson's DURABrite® pigment inks used in combination with Neenah Kimdura Poly media has been BS5609 certified.

³Failure is a random failure occurring during the random failure period.

Inkjet cartridge yields vary considerably for reasons including item printed, print settings, temperature and humidity. Yields may be lower when printing infrequently. A variable amount of ink remains in the cartridge after the replace cartridge" signal. Ink from the first cartridge is used for priming the printer. Ink is used for both printing and print head maintenance

⁵No character font or 1D/2D code font installed.





